

CA722/2



Pre Assembled Shorting Links

Internal Shorting Link Assemblies consist of a Current Bar shorting Sleeves and Screws. They install easily into the centre of the Terminal Block and connect to the current bar. They are available as standard 2, 3, 4, 10 or 100 pole assemblies and are ready for immediate installation.

PRODUCT SPECIFICATION

Torque	0.4 Nm
Rated Current	32 A

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CA722/2	Pre Assembled Shorting Link assemblies with 2 poles	100
CA722/3	Pre Assembled Shorting Links assemblies with 3 poles	100
CA722/4	Pre Assembled Shorting Links assemblies with 4 poles	100
CA722/10	Pre Assembled Shorting Links assemblies with 10 poles	10
CA722/100	Pre Assembled Shorting Links assemblies with 100 poles	10

SUITABLE FOR

CF4SPD2	4 sq.mm screw clamp diode D2 (1N5408) Configuration Terminal Block
CKT4SP	4 sq.mm Knife Type Disconnect & Test Terminal Blocks with Socket screws and with possibility of using Jumpers
CTL2.5U(I.S)	2.5 sq.mm Three Level internally shorted Terminal Blocks
CTL2.5UL	2.5 sq.mm Three Level Feed through Terminal Block with LED
CTS2.5UE	2.5 sq.mm, 6 mm thick Feed Through Terminal Block
CDLG4(I.S)	4 sq.mm Multiple Connection Earthing Terminal Blocks with 4 connection points.
CF4SPFT	4 sq.mm Standard Feed Through Terminal Blocks
CTL2.5U	2.5 sq.mm Three Level Feed through Terminal Blocks
CTL2.5UHL	2.5 sq.mm Three Level Terminal Blocks with LED suitable for sensor & actuator application
CTS4UN	4 sq.mm Standard Feed Through Terminal Blocks
CCC4U	Component carrier terminal block
CDL4UN	4 sq.mm Double Level Terminal Blocks.
CDL4UN(I.S)	4 sq.mm Double Level Internally Shorted Terminal Blocks.
CDLG4	4 sq.mm Double Level Earthing Terminal Blocks.
CF4SPD1	4 sq.mm screw clamp diode D (1N4007) Configuration Terminal Block
CF4SPL	4 sq.mm Single Level Fuse Terminal Blocks with LED indication.
CMC1-2	4 sq.mm Multiple Connection Terminal Blocks with 3 connection points.
CMC2-2	4 sq.mm Multiple Connection Terminal Blocks with 4 connection points.
CTL2.5UH	2.5 sq.mm Three Level Terminal Blocks suitable for sensor & actuator application
CTL2.5UH(I.S)D2	2.5 sq.mm Three Level Terminal Blocks with Diode suitable for sensor & actuator application
CF4SP	4 sq.mm Single Level Fuse Terminal Blocks with Jumper possibility
CF4SPD3	4 sq.mm screw clamp diode D3 (1N5820) Configuration Terminal Block
CKT4SPSC	4 sq.mm Knife Type Disconnect & Test Terminal Blocks with Socket screws spring loaded.